

HEAVY DUTY FORGED ALUMINUM WHEEL

Wheel Code	Wheel Size	Loading Capacity kgs	Tyre Size	Weight /kgs	Valve size	Rim/T (mm)	Disc/T (mm)	Vent hole	Vent hole size (mm)	NUT HOLE	Hole Diameter (mm)	Hole Type	PCD (mm)	CBD (mm)	Offset
C229001	22.5×9.00	4125	12R22.5	27	70MS	9.5	25	10	60	10	26	ISO	φ335	φ281.2	151.5/176.5
C229003	22.5×9.00	4125	12R22.5	24	70MS	7.5	24	10	60	10	26	ISO	φ335	φ281.2	152/176.5
C229073	22.5×9.00	4125	12R22.5	23.8	70MS	7.5	24	10	60	10	32	ISO	φ335	φ281.2	152.5/176.5
C229072	22.5×9.00	4125	12R22.5	26.8	70MS	9.3	25	10	60	10	32	ISO	φ335	φ281.2	151.5/176.5
C221100	22.5×11.75	4510	385/65R22.5	25.20	TR553E	10.4	24	10	40	10	26	ISO	φ335	φ281.2	0/24
C221101	22.5×11.75	4510	385/65R22.5	24.2	54MS	9	24.5	10	32	10	26	ISO	φ335	φ281.2	120/144.5
C221102	22.5×11.75	5000	385/65R22.5	27.3	54MS	10	26	10	32	10	26	ISO	φ335	φ281.2	120/146
C221103	22.5×11.75	5000	385/65R22.5	24.4	40MS	9.2	28	10	32.5	10	26	ISO	φ335	φ281.2	0/28
C221172	22.5×11.75	5000	385/65R22.5	27.1	54MS	10	26	10	32	10	32	ISO	φ335	φ281.2	120/146
C221173	22.5×11.75	5000	385/65R22.5	24.8	TR553E	10.2	24	10	40	10	32	ISO	φ335	φ281.2	0/24
C221105	22.5×11.75	5000	385/65R22.5	29.1	54MS	10	28	10	40	10	26	ISO	φ335	φ281.2	135/163
C221175	22.5×11.75	5000	385/65R22.5	29.1	54MS	10	28	10	40	10	32	ISO	φ335	φ281.2	135/163
C221300	22.5×13.00	5200	445/65R22.5	31.7	TR553E	13	30	10	40	10	26	ISO	φ335	φ281.2	- 15/15
C221402	22.5×14.00	5810	445/65R22.5	31.4	TR553E	13	25.4	10	40	10	26	ISO	φ335	φ281.2	0/25.4
C191400	19.5×14.00	5000	445/40R19.5	21.7	54MS	10.5	26.5	10	32	10	26	ISO	φ335	φ281.2	120/146.5

